



## AUC38 Series

C-Band to L/IF Down Converter

### Features

- Compact unit, complete in a single 1 RU package
- Full monitoring and control through LCD and keypad front panel or serial remote
- User selectable spectrum inversion
- Redundant ready
- Available for wide satellite bands
- Flexible design for various user's configurations
- RS232, RS485 and SNMP interface for remote M&C
- Built-in Redundancy control

### Reliability

Field proven with system deployed worldwide, Agilis IDU can withstand temperature from 0°C to +50°C up to 95% non-condensing humidity.

### Quality Assurance

All Agilis IDUs are designed and manufactured according to ISO 9001 Standard.

# AUC38 Series

## C-Band to L/IF Down Converter



## Technical Specifications

### Input Parameters

Input Frequency	3.4 to 4.2GHz
Impedance	50Ω
VSWR	1.3:1

### Output Parameters

Output Frequency	950-1750MHz (for C to L) 70 ± 18MHz (140MHz optional) (for C to IF)
Impedance	50Ω
VSWR	1.5:1
Output Power @P1dB	+5dBm min

### Transfer Parameters

Frequency spectrum	User selectable (for C to IF)
Conversion Gain	45dB min
Gain Adjustment	40dB with 0.5dB step
Gain Flatness	±0.75dB over 36MHz Bandwidth ±2dB over Full Bandwidth
Gain Stability	±0.25dB over 24hours at constant temperature
In Band Spurious	
Carrier dependent	-50dBc at max gain
Carrier Independent	-60dBm max
Out Band Spurious exclude LO	-60dBm max
Third order intermodulation products	40dBc @ two carriers 2MHz apart, 8dB back off from Prated for each carrier
Phase Noise	
@1KHz	-73dBc/Hz
@10KHz	-83dBc/Hz
@100KHz	-93dBc/Hz (for C to IF)
@1KHz	-75dBc/Hz
@10KHz	-85dBc/Hz
@100KHz	-95dBc/Hz (for C to L)

### Rear Panel Connections

IF/L Output	BNC Female (for C to IF) N-Type Female (for C to L)
RF Band Input	SMA Female
10MHz Ext REF Connector (Optional)	BNC Female
Remote Connector	DB 9 Female
Power IN	AC/DC

### Monitor and Control

Interface	RS232/ RS485/ SNMP (Optional)
Monitoring parameters	LO & Temperature Alarms
Control Parameters	Gain Adjustment @ 0.5dB Step

### Power Supply Requirement

AC Input Voltage	100 to 240VAC 50/60Hz
Power Consumption	35W

### Environmental

Operating temperature	0°C to 50°C
Humidity	up to 95% (Non-condensing)

### Mechanical

Dimension	480L x 330W x 44H mm
Weight	3.5kg (for C to L) 4.0kg (for C to IF)

\*All specifications are subject to change without notice.  
Rev. 300112



[avcomm.com.au](http://avcomm.com.au)

[info@avcomm.com.au](mailto:info@avcomm.com.au)

61 (02) 9939 4377

24/9 Powells Road, Brook Vale  
New South Wales 2100, Australia.

The word "Agilis" is written in a white, sans-serif font against a dark blue background. The letter 'A' is stylized with a white swoosh that extends to the right.